





Product Selector Guide

Model		Inputs	Outputs	Power Disconnect Relay	Power Sources	Certifications
PM8, PM8R Power Module		1 AC or DC	8C	-	1	UL Listed UL294
DAC8, DAC8R Direct Access Controller		8 Dry Contact	8SS	1-pole Relay with Aux Relay and Terminals	1 or 2	UL Listed UL294
MAC4, MAC4R Multi Access Controller		4 Dry Contact or Sink Powered	4FS, RI	1-pole Relay with Aux Relay and Terminals	1 or 2	UL Listed UL294
MAC8, MAC8R Multi Access Controller		8 Dry Contact or Sink Powered	8FS, RI	1-pole Relay with Aux Relay and Terminals	1 or 2	UL Listed UL294

Output Codes; **F** = Fail Safe (Fails on Fire Alarm)
P = Fail Secure (Stays Powered on Fire Alarm)
RI = Relay Isolated Outputs

C = Continuously Powered
SS = Semi-Selectable per Output thru Input wiring , F or P
FS = Fully Selectable per Output F, P, Dry Contacts or Fused-Output-Only

Notes;

- All R models use 2.5A Output PTCs, non-R models use 2.0A 3AG Fuses.
- All models with relays use depluggable, replaceable relays. Relays are included and can be ordered separately.
- All models are supplied with nylon mounting standoffs for sturdy installation.